

SYSTEM FOR SEARCHING DEVICE ON NETWORK

BACKGROUND OF THE INVENTION

Field of the Invention

5 The present invention relates to a system for searching a device on network, particularly to a device search system for displaying a searched device and position information.

Related Background Art

10 There has been heretofore provided, for example, a so-called directory service such as lightweight directory access protocol (LDAP) to efficiently find various resources such as a printer, a server, and a scanner (hereinafter also referred to as "device") on
15 network, and utilize the resources. The directory service functions as a telephone directory concerning so-called network, and is a service for managing and providing various information.

 Therefore, by utilizing the directory service and
20 searching the device connected to the network, a list of network addresses of usable devices on the network can be obtained.

 Additionally, the definitions in the LDAP are described in RFC1777 issued by IETF.

25 However, in the synopsis list, the comprehensible position information of the device for use cannot be obtained.

09612565.070700

For example, for a network printer as the device, a system has been demanded in which a user is notified of device hierarchical location information such as "the place of the printer closest to one's place on the floor" and "the place of the printer able to output a color image in the building" in a comprehensible manner.

Furthermore, another system has been demanded in which when an information processor on network is requested to execute printing or the like, the user is notified of information such as the place of the printer for the printing, the end state of one's requested printing, and the occurrence of errors such as jam and sheet shortage in the comprehensible manner.

Additionally, further system has been demanded in which the user is notified of the current status of the device (operation status, error occurrence status, and the like) in the comprehensible manner.

SUMMARY OF THE INVENTION

Wherefore, the present invention has been developed to remove the above-described disadvantage, and an object thereof is to provide a system in which the position, attribute, and status of a desired device on network can visually easily be grasped, so that the efficiency of operation using various devices on network can be enhanced.

According to a first aspect of the present invention, there is provided a network system comprising an information processor and a device. The device stores hierarchical position information

5 indicating the position of the device hierarchically and icon data indicating the device, and transmits the stored hierarchical position information and the icon data to the information processor. Moreover, the information processor displays the received icon data
10 together with the device position based on the received hierarchical position information.

Other objects and characteristics of the present invention will be apparent from the following description and drawings.

15
BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram showing the configuration of a network system to which the present invention is applied in a first embodiment.

20 Fig. 2 is a block diagram showing the inner configuration of a personal computer for use as a client or a server in the network system.

Fig. 3 is a block diagram showing the inner configuration of the device of the network system.

25 Fig. 4 is a block diagram showing the function of most characteristic configuration of the network system.

09612555.070700

Fig. 6 is an explanatory diagram showing device
5 information registered to the server by the device.

Fig. 8 is an explanatory view showing one example of icon information held by the device (color LBP).

Fig. 10 is an explanatory view of a search condition input screen of the client.

Fig. 12 is an explanatory view of a search condition formula for search information inputted in the search condition input screen.

Fig. 14 is an explanatory view of a first example of layout bit map information held by the client.

Fig. 16 is an explanatory view of a third example of layout bit map information held by the client.

Fig. 17 is an explanatory view of a fourth example of layout bit map information held by the client.

Fig. 18 is an explanatory view of one example of layout bit map information (UMP) held by the client.

5 Fig. 19 is an explanatory view of table information for associating and managing the layout bit map information with the location information.

10 Fig. 20 is an explanatory view of the first example when an icon indicating the device is displayed on the layout bit map in the client.

Fig. 21 is an explanatory view of the second example when the icon indicating the device is displayed on the layout bit map in the client.

15 Fig. 22 is an explanatory view of the third example when the icon indicating the device is displayed on the layout bit map in the client.

Fig. 23 is an explanatory view of the fourth example when the icon indicating the device is displayed on the layout bit map in the client.

20 Fig. 24 is an explanatory view of a response to a device status obtaining request issued to the device from the client.

25 Fig. 25 is an explanatory view of a processing for overlapping and displaying the icon indicating the device in a predetermined position on the layout bit map.

Fig. 26 is an explanatory view showing that the

09512565-070700

icon on the layout bit map is changed in accordance with the device status.

Fig. 27 is a flowchart showing the general process of the server.

5 Fig. 28 is a flowchart showing a device search processing in the server general process.

Fig. 29 is a flowchart showing the general process of the client.

10 Fig. 30 is a flowchart showing a device search request issue processing in the client general process.

Fig. 31 is a flowchart showing a device search result processing in the client general process.

15 Fig. 32 is a flowchart showing the status obtaining process of the device search result processing.

Fig. 33 is a flowchart showing a registration processing of device information of the device to the server.

20 Fig. 34 is a flowchart showing a response process to the device status obtaining request of the device.

Fig. 35 is a bit map list for the respective hierarchies to be searched in a second embodiment.

25 Fig. 36 is a flowchart showing a search result display processing performed by the search client in the second embodiment.

Fig. 37 is a diagram showing the layout bit map displayed when search is performed with "attribute = 0,

09612565 "070700

attribute value = ABC Trading Co., Ltd."

Fig. 38 is a diagram showing a result display when all the devices are searched on the condition "attribute = O, attribute value = ABC Trading Co., Ltd."

Fig. 39 is a diagram showing the layout bit map displayed when search is performed with "attribute = BR, attribute value = Tokyo Branch".

Fig. 40 is a diagram showing the result display when all the devices are searched on the condition "attribute = BR, attribute value = Tokyo Branch".

Fig. 41 is a diagram showing the layout bit map displayed when search is performed with "attribute = BU, attribute value = AA Building".

Fig. 42 is a diagram showing the result display when all the devices are searched on the condition "attribute = BU, attribute value = AA Building".

Fig. 43 is a diagram showing the layout bit map displayed when search is performed with "attribute = FL, attribute value = 2F".

Fig. 44 is a diagram showing the result display when all the devices are searched on the condition "attribute = FL, attribute value = 2F".

Fig. 45 is a diagram showing the layout bit map displayed when search is performed with "attribute = FL, attribute value = 1F".

Fig. 46 is a diagram showing the result display

004040"59527960

Fig. 47 is an explanatory view of one example of a storage medium in which a network device control program for performing the function of the present invention is stored.

Fig. 50 is a flowchart showing a client process in
10 the third embodiment.

Fig. 52 is a diagram of an event notice
15 destination management table held by the device in the
fourth embodiment.

20 Fig. 54 is an explanatory view of an event notice
returned to the client from the device in the fourth
embodiment.

25 Figs. 58 and 59 are flowcharts showing a device
process in the fourth embodiment.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Embodiments of the present invention will be described hereinafter in detail with reference to the drawings.

5 <First Embodiment>

The present invention is applied, for example, to a network system 100 shown in Fig. 1.

10 The network system 100 is used on office floors including first and second floors, and as shown in Fig. 1, personal computers (PC) 111, 113 as information processors on a client side, a personal computer (PC) 112 as the information processor on a server side, and various devices 101 to 105 are connected via LAN 150 so that communication can be performed with one another.

15 The PCs (client devices, hereinafter referred to simply as "client") 111, 113 as the information processors on the client side can execute the program of a network device search client in the present embodiment, issue inquiry information on the device
20 satisfying desired conditions to the PC (server device, hereinafter referred to simply as "server") 112 as the server side information processor, and display the obtained search result.

25 Moreover, in this example, the client 111 is constituted of a desktop PC, and the client 113 is constituted of a notebook-size PC.

The server 112 is a PC able to execute the program

004070700 004070700 004070700

of a network device search server in the present embodiment, and stores information on the devices 101 to 105 of the present system 100, and various devices (network device) of another network system 140,

5 receives a device search inquiry from the clients 111, 113, and returns the search result.

The PCs used as the clients 111, 113 and server 112 have similar configurations, and operate network device search client software or network device search server software (both hereinafter referred to as "network device search software") by the constitution in Fig. 2.

Specifically, as shown in Fig. 2, a PC 200 is provided with: a CPU 202 for controlling PC general process; a ROM 203 for storing various programs and data for the process control in the CPU 202; a RAM 204 including the main memory, operation area, and the like of the CPU 202; a mouse (MS) 214; a mouse controller (MC) 213 for controlling an instruction input from the mouse (MS) 214; a keyboard (KB) 209; a keyboard controller (KBC) 205 for controlling the instruction input from the keyboard (KB) 209 and pointing device (not shown); a CRT display 210; a CRT controller (CRTC) 206 for controlling display on the CRT display 210; a hard disk drive (HDD) 211 and floppy disk drive (FDD) 212 for storing various programs and data (boot program, various applications, edition file, user file,

004020" 9952960

5 bidirectionally exchanging data with the devices 101 to 105, other PCs or other network system 140 (see Fig. 1) via LAN 150, and these respective constituting units are interconnected via a system bus 201 so that they can communicate with one another.

15 On the other hand, the devices 101 to 105 are
constituted of a color printer, a copying machine, and
the like.

The main configurations of these devices 101 to 105 are similar to one another. For example, as shown in Fig. 3, the device is provided with: a CPU 2302 for controlling a device general process; a ROM 2303 for

15

20

25

00700568

[illegible]

076129507000

07612985-070700

[illegible]

07612965070700

realized by executing predetermined processing programs such as network device search software in the CPU 202, 2302 shown in Figs. 2 and 3.

As shown in Fig. 4, a client apparatus 20, a device 30, and a server apparatus 10 are disposed on a network 40.

The client apparatus 20 includes: a search request module 21, constituted, for example of a general-purpose computer, for transmitting a desired device search condition to the server apparatus and receiving the result; a display module 22 for visualizing/displaying the received search result; and the like.

The server apparatus 10 functions as a directory server including a database 11 for managing attribute information of the device on the network 40. In the database 11, identification information of the device on the network and various attribute information of the device are registered.

A search module 12 searches the device matching with the condition from the database 11 based on the device search condition received from the client apparatus 20, and transmits the search result to the client apparatus. A device attribute registration module 13 receives the device attribute from the device 30 or the like and registers the attribute in the database 11.

09612565-070700

The device 30 is provided with a function of providing the client apparatus 20 with various services, and comprises, for example, a scanner, a printer, or a facsimile machine. A device attribute transmission module 31 transmits its attribute information to the server apparatus 10 to make a registration request.

Additionally, in the example of Fig. 1, the minimum unit of the device search system is shown, and a plurality of client apparatuses and devices are disposed on the network.

Moreover, the device search system may be provided with a plurality of server apparatuses.

The configuration and general process of the network system will be described hereinafter in detail. [Location Information of Device managed by Server 112]

The device location information is managed by the hierarchical structure shown in Fig. 5 by the server 112.

In Fig. 5, the location information of the color LBP 101 shown, for example, by device name (nm) "LBP1110" is designated as follows, as shown by "301", "308":

(C = JP (501), o = ABC Trading Co., Ltd. (502),
BR = Tokyo Branch (503), op = extend (504),
BU = AA Building (505), fl = 2F (506),
BL = 2-1 (507), dv = printer (508)).

09612565-070700

Respective entries C, O, BR, OP, BU, FL, BL, DV, UM, MAP are as follows:

C: country name ("JP" indicates Japan, "US" indicates America, and the like);

5 O: organization ("ABC Trading Co., Ltd.", "XYZ Products Company", and the like);

BR: branch, affiliate, and the like ("Tokyo Branch", "Osaka Branch", and the like);

10 OP : the presence of option information ("extend" indicates extension);

BU: building name ("AA Building", "BB Building", and the like);

FL: floor number ("1F", "2F", and the like);

BL: floor block ("1-1", "2-1", and the like);

15 DV: device ("printer", "MFP", and the like);

UM: device name ("LBP1110", "LBP3310", and the like); and

20 MAP: coordinates on the device map described later ("10X+10Y", and the like), and the respective entry attributes indicate attribute values of the respective determined ranges (values).

25 Additionally, the information may be set in the other hierarchy of the option information, or may be of data structure without setting the hierarchy of the option information.

In the present embodiment, by managing the location information of the devices on the network (the

09612565-070700

5

10

20

25

Moreover, a location information TAG 901 is added to the top of the location information 902, 903, a

device attribute information TAG 912 is added to the attribute information 913, 914, various information included in the device information can therefore be identified on the reception side (server 112) of the device information.

Fig. 6 shows the device information held by the color LBP 101 of the present system 100 as one example, and the location information 902, 911 is set in the device information. The location information indicates that the color LBP 101 is as follows:

device name NM = LBP 1110;

coordinate MAP on layout bit map = 10X+10Y;

device DV = printer,

and indicates in accordance with the hierarchical

location information shown in Fig. 5 that the color LBP 101 exists in a place shown by the following:

block BL of floor on which device is located = 2-1;

floor number FL of the floor = 2F;

building name BU of the floor = AA Building;

presence of option information OP = extend;

branch name BR = Tokyo Branch;

organization name O = ABC Trading Co., Ltd.;

country name C = Japan (JP).

Moreover, as the attribute information 913, 914, color attribute 913 indicating whether or not color input/output is possible, and IP address 914 indicating

09612555-070700

Therefore, when the above-described device
5 information is given to the server 112 from each
device, the server 112 manages the device information
of each device by the database as shown in Fig. 7.

In the example of the database shown in Fig. 7, the attribute information (902 to 914) are associated with the respective devices 101 to 105 and stored.

20 The server 112 searches the device based on the device search request from the clients 111, 113 (device matching with the search condition inputted from the user) from the database shown in Fig. 7.

The device information obtained by the search is
25 returned to the client as a device search request
sender.

Each device stores icon information for various events which possibly occur in the device in a memory unit.

10 Moreover, the MFP 102 holds icon information indicating the operated state (ready), icon information indicating the paper shortage state (no paper), and icon information indicating the jam occurrence state (paper jammed) as shown in Fig. 9.

Moreover, the device reads the icon information indicating the current device state from the memory unit in response to the request from the client, and
20 transmits the information to the client as the request sender.

Additionally, the icon information held by the device is not limited to the icon information shown in Figs. 8 and 9, and for example, an icon indicating that the device is being used, and an icon indicating occurrence of a read/write error in the hard disk or the like mounted on the device may be used. Moreover, when the device is FAX, an icon indicating that

transmission/reception is being performed may be provided. Furthermore, when an icon indicating authentication error occurrence is displayed/outputted on MAP on the client side, the client side can promptly recognize the authentication error occurrence in the device, and it is therefore possible to monitor unfair invasion from a remote plate.

[Search Condition Input Operation by Clients 111, 113]

Fig. 10 shows a screen in which the user inputs the condition for searching the desired device in the clients 111, 113 (search condition input screen). This screen is displayed, for example, on the CRT 210, and various search conditions can be inputted by the mouse 214 and keyboard 209 (see Fig. 2).

In Fig. 10, in input columns shown by "1001a", "1001b", "1001c", the entry of the search object device is inputted. Here, the entry can directly be inputted, but by operating the right end of the input column (black triangular mark), and displaying a pull-down menu, the desired entry can be selected from the menu.

In input columns shown by "1002a", "1002b", "1002c", the attribute information corresponding to the entries inputted in the input columns 1001a, 1001b, 1001c are inputted.

For these input columns 1002a, 1002b, 1002c, similarly to the input columns 1001a, 1001b, 1001c, both the direct input and the input from the pull-down

09612565-070700

menu are possible. For example, when the entry
inputted in the input column 1001a is "device", by
operating the right end of the input column 1002a, the
pull-down menu of the printer, MFP, and scanner as the
5 device attribute information is displayed. Therefore,
when the desired attribute information is selected from
the pull-down menu, the selected attribute information
is set in the input column 1002a.

In columns shown by "1003a" and "1003b", the
10 correlating of the respective information inputted in
the input columns 1001a to 1001c, 1002a to 1002c by
"AND" is designated, and in columns shown by "1004a"
and "1004b", the correlating of the respective
information inputted in the input columns 1001a to
15 1001c, 1002a to 1002c by "OR" is designated.

Section "1005" indicates a search start button.
By operating the search start button 1005, the device
search in the server 112 is started based on the input
to the input columns 1001a to 1001c, 1002a to 1002c,
20 and the designation by the designation column 1003a,
1003b, 1004a, 1004b.

Fig. 11 shows an input example in the search
condition input screen shown in Fig. 10.

In Fig. 11, "the search object device is a
25 printer", and "the printer can perform color output"
are inputted as the search condition.

Additionally, as the search conditions,

09612565-070700

installation place conditions such as "a printer whose installation floor is the second floor" (see the input columns 1001c and 1002c of Fig. 11) and other various conditions can further be added. Here, for the

5 simplicity of description, "the search object device is a printer" and "the printer can perform color output" are described as the inputted search condition.

For example, in the client 111, as shown in Fig. 11, when the search condition of "the search object
10 device is a printer" and "the printer can perform color output" is inputted, and the search start button 1005 is depressed in the input state, the search condition is obtained as a search condition formula as shown in Fig. 12. As shown in Fig. 12, as the search condition
15 formula, for the search condition shown in Fig. 11, the printer is indicated as the search object device (DV) and the condition that the color output is possible (TRUE) is indicated.

Subsequently, in response to depression of the
20 search start button 1005, the search condition inputted in the input screen is transmitted to the server 112 as the search request.

According to the search condition input example shown in Fig. 11, the search condition shown in Fig. 12
25 is issued to the server 112.

On the other hand, the server 112 having received the search condition shown in Fig. 12 searches the

09612565-070700

device matching with the search condition formula of Fig. 12 from a database 900. For example, the device as the printer able to perform color output is searched from the devices 101 to 105 shown in the table. Here, only the device 101 (color LBP) corresponds to this.

Therefore, the server 112 returns the device information (location information, attribute information, and icon information) of the color LBP 101 shown in Fig. 13 as the search result to the client 111.

Additionally, when a plurality of devices matching with the search condition formula from the client are searched, the search result shown in Fig. 13 is constituted of a plurality of pieces of device information.

[Search Result Display in Clients 111, 113]

First, each of the clients 111, 113 holds MAP information (layout bit map information) of various places where the device shown by the hierarchical structure of the location information shown in Fig. 5 would be installed in the memory unit.

Figs. 14 to 18 show MAP information of the first and second floors in C = Japan (JP), O = ABC Trading Co., Ltd., BR = Tokyo Branch, BU = AA Building as one example of MAP information held by the client.

Here, for the MAP information, actual desk arrangement and partition state on each floor are

09612555-070700

preset as a bit map.

Fig. 14 shows MAP information MP1-1 of one block of the first floor, Fig. 15 shows MAP information MP1-2 of two blocks of the first floor, Fig. 16 shows MAP information MP2-1 of one block of the second floor, and Fig. 17 shows MAP information MP2-2 of two blocks of the second floor.

Fig. 18 shows MAP (unknown MAP) information UMP for use, for example, when the MAP information corresponding to the location information included in the search result from the server 112 is held in the memory unit (there is no attribute value), or when there is no location information in the device information of the device searched by the server 112 (the device holds no location information), or when the corresponding device is not searched by the server 112.

In the MAP information UMP shown in Fig. 18, a message indicating that there is no MAP information is displayed in column "1901", and column "1902" displays an icon of a device able to be searched in the server 112 but including no location information, or an icon of the search object device unable to be searched.

For the MAP information as shown in Figs. 14 to 18, the correspondence with each block (BL) is managed as a MAP correspondence table as shown in Fig. 19. In the example of Fig. 19, the MAP information is managed for the blocks 1-1, 2-2 of the first and second floors,

09612565-070700

Therefore, when location information "1401" in Fig. 19 is designated, the MAP information is selected based on the information of the floor (FL) hierarchy and block (BL) hierarchy and the MAP correspondence table of Fig. 19, and displayed on the CRT 210.

Therefore, the position, block, and floor of the desired device can visually be indicated.

As shown in Figs. 20 to 23, the installation position, block, and floor of the desired device, server and client can securely be grasped at one glance.

[Search Result Display in Clients 111, 113]

The client 111 periodically issues a device status obtaining request to the device, obtains the status information from the device, and reflects the information on the icon display on the MAP.

In response to the device status obtaining request from the client 111, the device transmits the icon information corresponding to the status to be notified

The client 111 overlaps and displays the icon information received from the device on the MAP, and the device status is comprehensibly notified to the user.

The color LBP 101 responds to the reception of the device status obtaining request, recognizes its current state, obtains the icon information corresponding to the current state, and transmits the obtained icon information to the client 111.

When the client 111 receives the response packet shown in Fig. 24, the icon information included in the

response packet is overlapped and displayed in the predetermined position on the MAP as described above. Since the display of the icon information is executed for every reception of the response packet, as a
5 result, the corresponding icon information is displayed on the MAP in accordance with the current status of the color LBP 101.

Additionally, the display of the icon information may be executed only when there is a change in the
10 periodically received icon information.

Therefore, for example, when the color LBP 101 changes from the operated state to the jam occurrence state, the icon information on the MAP in the client 111 is also changed from the icon information
15 indicating the operated state to the icon information indicating the jam occurrence state and displayed. Consequently, not only the position, block and floor of the device but also the current status of the device can constantly and explicitly be indicated.

20 Fig. 25 shows the arrangement of the icon on the MAP when the icon is overlapped and displayed on the MAP in accordance with the device status as described above.

Here, as a result of search in the server 112, it
25 is indicated that the color LBP 101 installed in block 2-1 on the second floor is searched, the coordinate MAP on the MAP included in the location information is

09612555 070700

Therefore, the icon indicating the paper shortage state as shown in Fig. 25 is disposed, overlapped and displayed in the coordinate 10X+10Y on MAP information MP2-1 shown in Fig. 16 (MAP information of block 2-1 of the second floor). As a result, the display screen of the CRT 210 obtains a screen state as shown in Fig. 26.

```
[Processing Flow in Server 112, Clients 111, 113, and
Devices]
```

Additionally, the flowcharts of Figs. 27 to 34 show processing programs executed in the server 112,

clients 111, 113, and respective devices.

Specifically, by executing the processing programs shown in the flowcharts of Figs. 27 to 34 by the CPU (201, 2302) of the server 112, clients 111, 113, and

5 respective devices, the following process by the function shown in Fig. 4 is realized.

(1) Registration Process of Device Location

Information: see Fig. 33

10 Here, for the simplicity of description, among various devices, the color LBP 101 is noted, and the location information registration process will be described.

15 The color LBP 101 holds the device information including the location and attribute information in the nonvolatile RAM 2312.

When power turns on, the CPU 2302 performs connection to the server 112 (step S3001).

20 When the connection to the server 112 is established, the device information held in the nonvolatile RAM 2312 is read, and registered in the server 112 in accordance with the format shown in Fig. 6 (step S3002).

25 After finishing the registration to the server 112, the CPU 2302 releases the connection to the server 112 (step S3003).

After the power turns on, the respective devices including the color LBP 101 register the device

09612565 "070700

information of the devices themselves to the server
112.

(2) General Process of Server 112: see Fig. 27

The processing program executed in the server 112
5 is constituted of an event drive type program. When a
certain event occurs, the event is analyzed, and the
corresponding processing is executed.

Additionally, for the simplicity of the
description, among various processings executed in the
10 server 112, mainly the device search processing and
device information registration processing will be
described.

In the server 112, when power turns on, the CPU
202 opens a receiving port (step S2401), and obtains
15 the event (step S2402).

Subsequently, the CPU 202 judges whether the event
obtained in the step S2402 is an end command or not
(step S2403).

As a result of judgment in the step S2403, when
20 the obtained event is the end command, the CPU 202
closes the receiving port opened in the step S2401
(step S2404), and ends the present processing.

As a result of judgment in the step S2403, when
the obtained event is not the end command, the CPU 202
25 judges whether the obtained event is a device search
request from the client (inquiry request) or not (step
S2405).

09612565.070700

As a result of judgment of step S2403, when the obtained event is the device search request, the CPU 202 executes a device search processing (step S2406). Thereafter, the CPU returns to the step S2402, and repeatedly executes the subsequent processing steps.

Additionally, the processing of step S2406 will be described later in detail.

As a result of judgment of the step S2403, when the obtained event is not the device search request, the CPU 202 judges that the event is a registration request of device information from the device, and executes a device information registration processing (step S2407).

Specifically, the device information from each device is registered to the database shown in Fig. 7. This table information is stored in the hard disk drive (HDD) 211.

(2-1) Device Search Processing (Step S2406): see Fig. 28

The present processing is repeatedly executed until the processing for all the search conditions included in the device search request from the client (here, client 111) is ended with respect to the device information registered in Fig. 7.

In the server 112, the CPU 202 first judges whether the processing from step S2503 by a device search unit 413 is completely executed with respect to

09612565-070700

all search conditions in the device search request
(received packet) from the client 111 (step S2501).

As a result of judgment of the step S2501, when
the processing for all the search conditions is ended,
5 the device information of the searched device (location
information, attribute information) is returned as the
search result to the client 111 as the device search
request issuer (step S2502).

After ending the processing of the present step
10 S2502, the present processing ends.

On the other hand, as a result of judgment of the
step S2501, when the processing for all the search
conditions is not ended, the search condition included
in the device search request is successively retrieved
15 (step S2503).

Subsequently, in order to obtain the device
information satisfying the search condition retrieved
in the step S2503, it is judged whether or not all the
device information registered in Fig. 7 is searched
20 (step S2504).

As a result of judgment of the step S2504, when
the search for all the device information is ended, the
CPU 202 having recognized this returns to the step
S2501 to execute a processing for the next search
25 condition, and repeatedly executes the subsequent
processing steps.

As a result of judgment of the step S2504, when

09612565-070700

the search for all the device information is not ended,
the device information indicated by counter n for
successively searching all the device information is
obtained from the device information registered in Fig.

5 7 (step S2505).

It is judged whether or not the device information
obtained in the step S2505 matches with the object
search condition (step S2506).

As a result of judgment of the step S2506, when
10 the object device information fails to match with the
object search condition, the CPU counts up the counter
n, then returns to the step S2504 to execute a
processing for the next device information, and
repeatedly executes the subsequent processing step.

As a result of judgment of the step S2506, when
15 the object device information matches with the object
search condition, the device information is obtained
from the database (step S2507), and the information is
added to the search result to be transmitted to the
20 client 111 in the step S2502 (step S2508).

Thereafter, the CPU counts up the counter n, then
returns to the step S2504 to execute the processing for
the next device information, and repeatedly executes
the subsequent processing step.

25 Additionally, in the step S2508, the device
information satisfying the individual search conditions
can be obtained as the search result. However, for

09612565-070700

example, when the individual search conditions are interconnected via "AND", among the device information obtained in the step S2508, only the device information satisfying all the search conditions is finally

5 transmitted to the client 111.

(3) General Process of Clients 111, 113: see Fig. 29

The processing program executed in the clients 111, 113 is constituted of the event drive type program. When a certain event occurs, the event is
10 analyzed, and the corresponding processing is executed.

Moreover, the clients 111, 113 start a status obtaining process (program) as occasion demands. The status obtaining process is a process of periodically inquiring of the current device status with respect to
15 the found device as the device search result returned from the server 112 (device status obtaining request), and displaying the icon indicating the device status in an appropriate position on the layout bit map in accordance with the device status information
20 transmitted as the response (polling notice system).

Additionally, for the simplicity of description, here the client 111 is noted, and the process thereof will be described.

In the client 111, the CPU 202 obtains the event
25 (step S2601).

Subsequently, the CPU 202 judges whether or not the event obtained in the step S2601 is an end command

09612565-070700

(step S2605).

As a result of judgment of the step S2605, when the obtained event is the search result, the CPU 202 executes a search result processing including a
5 processing of displaying the search result on the CRT 210, a processing of obtaining the device status, a processing of changing the icon on the MAP displayed on the CRT 210, and the like (step S2606).

Thereafter, the CPU 202 returns to the step S2061,
10 and repeatedly executes the subsequent processing steps.

Additionally, the processing of the step S2606 will be described later in detail.

As a result of judgment of the step S2605, when
15 the obtained event is not the search result, that is, when the obtained event is not any one of the end command, device search command, and device search result, the CPU 202 executes a processing corresponding to the obtained event (step S2607).

20 Thereafter, the CPU 202 returns to the step S2061, and repeatedly executes the subsequent processing steps.

(3-1) Device Search Request Issue Processing (Step S2604): see Fig. 30

25 First, the search condition inputted from the user is obtained from the search condition input screen shown in Fig. 10 (step S2701).

09612565-070700

5 generated, and a device search request is issued to the
server 112 (step S2702).

10

15

20

25

Thereafter, with respect to the respective search results saved in the hard disk drive (HDD) 211, the following status obtaining process is executed (step

S2803).

Thereafter, the present processing ends.

(3-2-1) Status Obtaining Process (Step S2803): see
Fig. 32

5 The present process is a program for obtaining the
device status at a certain constant interval, and
displaying the icon in accordance with the device
status on the MAP.

10 When the present process is executed, the CPU 202
first judges with respect to all the search results
held in the hard disk drive (HDD) 211 by the step S2802
(see Fig. 31) whether or not the processing from step
S2902 is executed (step S2901).

15 As a result of judgment of the step S2901, when
the processing for all the search results is completely
executed, the CPU 202 starts a polling timer (inner
timer or the like) to obtain the device status at the
certain interval (step S2913).

20 Thereafter, the CPU waits for a time-out event of
the polling timer (step S2914). In this state, when
the time-out event of the polling timer is generated,
the CPU returns to the step S2901, and executes the
subsequent processing steps again.

25 As a result of judgment of the step S2901, when
the processing for all the search results is not
executed, the processing from the next S2902 is
executed.

091612555-070700

Specifically, first the device information for one device is obtained from the unprocessed search result in the hard disk drive (HDD) 211 (step S2902).

Subsequently, IP address of the device information
5 obtained in the step S2901 is used as the address, and the device status obtaining request is transmitted (step S2903).

For example, with the processing for the device information shown in Fig. 13, since the IP address is
10 "192.1.2.1", the device status obtaining request packet is transmitted to this address.

Thereafter, the CPU waits for a response to the device status obtaining request packet shown in Fig. 24 from the device corresponding to the address of the
15 device status obtaining request packet.

When the response packet is received from the device of the address of the device status obtaining request (the device corresponding to the device information obtained in the step S2902) (step S2904),
20 the icon information (see Fig. 24) included in the response packet is obtained (step S2905).

Subsequently, it is judged whether or not the MAP information corresponding to the information (see Fig. 13) indicated by "BL" of the device information
25 obtained in the step S2902 is held by MAP correspondence table shown in Fig. 19 (step S2906).

Concretely, by referring to the MAP correspondence

09612565 "070700

5

10

15

20

25

is now in the paper shortage occurrence state, on the CRT 210, the screen of the icon indicating that the color LBP 101 is in the paper shortage occurrence state is displayed.

5 Thereafter, the CPU returns to the step S2901 to execute the processing for the next search result, and repeatedly executes the subsequent processing step.

 As a result of judgment of the step S2907, when the MAP corresponding to the CRT 210 is not displayed,
10 the MAP is displayed on the CRT 210 (step S2908).

 Thereafter, the CPU advances to the step S2909, and executes a processing for overlapping and displaying the icon on the MAP.

 As a result of judgment of the step S2906, when
15 MAP display is not possible, it is judged whether or not unknown MAP information shown in Fig. 18 is now displayed on the CRT 210 (step S2910).

 As a result of judgment of the step S2910, when the unknown MAP is displayed on the CRT 210, the icon
20 obtained in the step S2905 is displayed in a device column (column "2902" of Fig. 16) on the unknown MAP. As a result, the icon of the device whose location information is unregistered is displayed in the device column on the unknown MAP.

25 Thereafter, the CPU returns to the step S2901 to execute the processing for the next search result, and repeatedly executes the subsequent processing step.

09612565 "070700

Thereafter, the CPU advances to the step S2912,
5 and executes a processing for displaying the icon in
the icon column of the MAP.

Here, for the simplicity of description, among
10 various devices the color LBP 101 is noted, and the
response process to the device status obtaining request
(device status response process) will be described.

By the processing of the step S3101, the device status obtaining request from a certain client (here, client 111) is received (step S3102), the status of the device (color LBP 101) is examined, and the icon information to be notified to the client 111 is determined (step S3103). For example, when the paper shortage occurs in the color LBP 101, among various icon information held in the memory unit, the icon information indicating "paper shortage" is determined as the icon information to be notified to the client 111.

5 generated (step S3104), and transmitted to the client
111 (step S3105).

10 As described above, in the present embodiment,
when in the clients 111, 113, the position information
of the device matching with the search condition
designated by the user is obtained, and the device icon
is displayed on the MAP, the user can easily understand
15 the device and position.

20 communication with the device corresponding to the icon
on the MAP by the polling system, the user can visually
and easily know the device status. Therefore, the user
can efficiently select and use the usable device.

Moreover, in the present embodiment, since in the
25 clients 111, 113, the icon information (device bit map
icon information) indicating the device status is
directly obtained from the device during the device

5
10

15

15

20

25

25

method.

Fig. 35 is a diagram showing a bit map list corresponding to each hierarchy to be searched (hereinafter referred to as "bit map correspondence list").

A list shown below the bit map correspondence list corresponds to management information of MAP information shown in Fig. 19.

In the present embodiment, the icon information (device bit map icon) is displayed based on the attribute information right subordinate to the attribute of the hierarchy to be searched. The hierarchical relation is shown in Fig. 5.

For example, when all the devices are searched on the search condition of "BU = AA Building", the right subordinate attribute FL (see Fig. 5) is used as the position information for displaying the icon of the device, and displayed on the layout bit map.

First a processing of displaying the search result on the client side will be described.

For example, when all the devices in ABC Trading Co., Ltd. are searched, the user on the client side (client 111) selects and inputs "company name (0)" in the input column 1001a of the search item from the pull-down menu on the search condition input screen shown in Fig. 10, inputs "ABC Trading Co., Ltd." in the input column 1002a of the attribute value, and

09512565-070700

Then the client 111 having executed the device search obtains the search result from the server 112 with the procedure described in the first embodiment. Subsequently, the client 111 overlaps and displays the device bit map icon on the layout bit map based on the search result obtained from the server 112.

Specifically, when the search result display processing starts, it is judged whether the display of all obtained search results is finished (step S6001), and the display processing is all repeated until all the results are processed.

Subsequently, it is judged whether the layout bit map corresponding to the attribute of the searched condition has been already displayed (step S6003).

25 Here, since the search is executed on the
condition "attribute = 0, attribute value = ABC Trading
Co., Ltd.", by referring to the bit map correspondence

list shown in Fig. 35, the device bit map icon of the search result is displayed on the layout bit map MP101 as shown in Fig. 37. Therefore, it is judged in the step S6003 whether the layout bit map MP101 of Fig. 37 has been already displayed.

As a result of judgment of the step S6003, when the layout bit map is not displayed, the corresponding layout bit map is displayed on the screen (step S6004), the process shifts to a processing of the next step S6005.

On the other hand, as a result of judgment of the step S6003, when the layout bit map is already displayed, the processing of the step S6004 is skipped, the lower layer attribute of the searched attribute and the attribute value are obtained from the search result (step S6005).

Subsequently, it is judged whether the obtained lower layer attribute value can be displayed (step S6006).

As a result of the judgment, when the attribute value of the device is not out of the range, or the attribute value is not inputted, it is judged that the display is impossible, and the process advances to step S6011.

It is judged in the step S6011 whether the map UMP is already displayed. When the map is not displayed, Unknown map UMP is displayed (step S6012).

09612565.070700

Subsequently, the device bit map icon corresponding to the device name (NM value) obtained in the step S6002 is displayed in the device column 1902 of Unknown map UMP (step S6013).

5 On the other hand, as a result of judgment of the step S6006, when the obtained lower layer attribute value can be displayed, it is judged whether the lower layer attribute is MAP attribute (icon display coordinate information) (step S6007).

10 As a result of the judgment, when the attribute is not MAP attribute, the device bit map icon corresponding to the device name (NM value) obtained in the step S6002 is overlapped and displayed in the attribute position on the displayed layout bit map
15 (step S6008). Here, since in the hierarchical location information the attribute value of the layer BR under the layer 0 is "Tokyo Branch" (see Fig. 5), the icon corresponding to the obtained device name is displayed in the position of Tokyo Branch 5001. As a result, the
20 display is obtained as shown in Fig. 38.

Moreover, when the device position is searched in more detail, the user selects "block name (BL)" from the pull-down menu, and inputs "block name (BL)" in the input column 1001a of the search item on the search
25 condition input screen of Fig. 10, inputs "2-1" in the input column 1002a of the attribute value, and depresses the search start button 1005 to execute

09612565.070700

device search.

Thereby, the client 111 obtains the search result from the server 112 in the procedure described in the first embodiment. Subsequently, the client 111

5 overlaps and displays the device bit map icon on the layout bit map based on the search result obtained from the search server PC. Also in this case, the processing flow of Fig. 36 is executed.

10 In this case, as a result of judgment of the step S6007, the lower layer attribute obtained in the step S6005 is MAP attribute, and the process therefore advances to step S6009.

15 It is judged in the step S6009 whether the coordinate range shown in the MAP information is in a range of the layout bit map. Subsequently, within the range, the device bit map icon corresponding to the device name (NM value) obtained in the step S6002 is overlapped and displayed in the coordinate position of the displayed layout bit map (step S6010).

20 Here, since the search is executed on the condition "attribute = BL, attribute value = 2-1", by referring to the bit map correspondence list shown in Fig. 35, the device icon of the search result is displayed on the layout bit map MP2-1 shown in Fig. 16.

25 Moreover, since the attribute subordinate to the attribute BL of the hierarchical location information is MAP attribute (see Fig. 5), the icon indicating each

09612565.070700

5 Additionally, as a result of judgment of the step
S6009, when the coordinate range indicated by the MAP
information is not in the range of the layout bit map,
the process advances to step S6013 to display the
device bit map icon corresponding to the device name
(NM value) obtained in the step S6002 is displayed in
0 the device column 1902 of Unknown map UMP.

As described above, Fig. 37 shows layout bit map MP101 for use in the search on "attribute = 0,
15 attribute value = ABC Trading Co., Ltd.". In this case, the device bit map icon of the device whose attribute value of the lower layer attribute BR of the attribute 0 is "Tokyo Branch" is displayed in 5001, and
20 the device bit map icon of the device whose attribute value is "Osaka Branch" is displayed in layout bit map 5002.

Fig. 39 shows a layout bit map MP102 for use in the search on condition "attribute = BR, attribute

value = Tokyo Branch". In this case, the lower layer attribute of the attribute BR is OP, the OP indicates OPTION, and it is indicated that detailed information is present in further lower layer. The device bit map icon of the device in which the attribute value of the attribute BU is AA Building is displayed in a layout bit map 5201.

Therefore, when all the devices are searched on condition "attribute = BR, attribute value = Tokyo Branch", the result is displayed as shown in Fig. 40, and the device bit map icon of the device present in the AA Building is displayed in the layout bit map 5201 as shown in Fig. 40.

Fig. 41 shows a layout bit map MP103 for use in the search on condition "attribute = BU, attribute value = AA Building". In this case, the device bit map icon of the device in which the attribute value of the lower layer attribute FL of the attribute BU is 2F is displayed on a layout bit map 5402, and the device bit map icon of the device whose attribute value is 1F is displayed on a layout bit map 5401.

Therefore, when all the devices are searched on condition "attribute = BU, attribute value = AA Building", the result is displayed as shown in Fig. 42, and the device bit map icons of all the devices present in 2F floor are displayed in the layout bit map 5402, and the device bit map icons of all the devices present

004020"5952T960

in 1F floor are displayed in the layout bit map 5401 as shown in Fig. 42.

Fig. 43 shows a layout bit map MP104 for use in the search on condition "attribute = FL, attribute value = 2F". In this case, the device bit map icon of the device in which the attribute value of the lower layer attribute BL of the attribute FL is "2-1" is displayed on a layout bit map 5601, and the device bit map icon of the device whose attribute value is "2-2" is displayed on a layout bit map 5602.

Therefore, when all the devices are searched on condition "attribute = FL, attribute value = 2F", the result is displayed as shown in Fig. 44, and the device bit map icons of all the devices present in 2F-1 are displayed on the layout bit map 5601, and the device bit map icons of all the devices present in 2F-2 are displayed on the layout bit map 5602 as shown in Fig. 44.

Fig. 45 shows a layout bit map MP105 for use in the search on condition "attribute = FL, attribute value = 1F".

In this case, for the search result display, the device bit map icon of the device in which the attribute value of the lower layer attribute BL of the attribute FL is "1-2" is displayed on a layout bit map 5801, and the device bit map icon of the device whose attribute value is "1-1" is displayed on a layout bit

09612565 "070700

for returning the corresponding MAP information to the client as the MAP information requester.

Fig. 49 is a flowchart of the processing of the step S4808 of Fig. 48 in the server 112, that is, a MAP information transmission processing.

First, when the MAP information obtaining request (MAP information download request) is received from the client (step S4901), it is judged whether or not the MAP information corresponding to the location information included in the MAP information obtaining request is held (step S4902).

Concretely, for example, by referring to the correspondence table shown in Fig. 19, and judging whether the MAP information corresponding to the location information notified from the client is present or not, it is judged whether or not MAP display is possible in the client 111.

Additionally, here, when the location information in the device information includes the respective information shown in "1401" of Fig. 19, it is judged that MAP display is possible.

As a result of judgment of the step S4902, when the MAP display is possible in the client 111, the MAP information corresponding to the location information notified from the client is obtained from the memory unit, and transmitted to the client 111 (step S4903).

As a result of judgment of the step S4902, when

09612565-070700

the MAP display is impossible in the client 111, the unknown MAP information UMP shown in Fig. 18 is obtained from the memory unit, and transmitted to the client 111 (step S4904).

5 By the processing shown in Figs. 48, 49, the server 112 can transmit the MAP information requested from the client to the client as the requester.

 A processing of receiving the MAP information from the server 112 from the client will next be described
10 with reference to a flowchart of Fig. 50.

 Fig. 50 is a flowchart showing a status obtaining process started in the step S2803 of the search result display processing (Fig. 31) in the client. The status obtaining process is executed in the first embodiment
15 based on the processing of the flowchart of Fig. 32, but in the third embodiment based on the flowchart of Fig. 50.

 When the status obtaining process is executed, first the CPU 202 judges, with respect to all the
20 search results held in the hard disk drive (HDD) 211 by the step S2802 (see Fig. 31), whether or not the processing from step S5002 is executed (step S5001).

 As a result of judgment of the step S5001, when all the search results are processed, the CPU 202
25 starts the polling timer (inner timer or the like) to obtain the device status at the certain interval (step S5013).

09612555-070700

5

processing from the next S5002 is executed.

10

15

is transmitted to this address.

20

25

the icon information (see Fig. 24) included in the response packet is obtained (step S5005).

Subsequently, it is judged whether or not the MAP information corresponding to the information indicated
5 by the location information (BL information or the like: see Fig. 13) of the device information obtained by the step S5002 is already displayed on the CRT 210 (step S5006).

As a result of judgment of the step S5006, when
10 the MAP information is displayed on the CRT 210, the icon information obtained in the step S5005 is overlapped and displayed in the position indicated by coordinate information MAP of the device information with respect to the MAP information (step S5009).

Therefore, the CPU returns to the step S5001 to
15 execute the processing for the next search result, and repeatedly executes the subsequent processing step.

As a result of judgment of the step S5006, when
the MAP information is not displayed on the CRT 210,
20 the MAP information corresponding to the location information of the device information is obtained (step S5007).

Specifically, the MAP information obtaining
request including the location information of the
25 device information is transmitted to the server 112. After the MAP information obtaining request is transmitted, the MAP information (or unknown MAP

09612555-070700

information) corresponding to the location information of the device information is received from the server 112.

Subsequently, the MAP information obtained in the step S5007 is displayed on the CRT 210 (step S5008).

Thereafter, the process advances to the step S5009, and a processing of overlapping and displaying the icon on the MAP is executed.

Thereby, for example, with the processing for the device information as shown in Fig. 13, since BL information is "2-1", MAP information MP2-1 shown in Fig. 16 is transmitted as MAP from the server 112, and the icon indicating the current status of the device of the object device information is displayed in the position indicated by the coordinate information MAP (= 10X+10Y) on the MAP.

The third embodiment has been described above.

Additionally, in the first embodiment, since the layout bit map is held by the client 111, during the display of the search result on the client 111, it is unnecessary to transfer the layout bit map to the client 111 from the server 112, the processing and time during the display can be reduced, and the traffic of the network system can effectively be reduced.

On the other hand, in the third embodiment, since the layout bit map is held by the server 112, the map information can one-dimensionally be managed in the

09612565 "070700

server apparatus, the necessity of holding the unnecessary map information by the client 111 is obviated, update and other maintenance processes can be facilitated, and the load of the memory resource of the client 111 can effectively be reduced.

Therefore, by considering the network load and client ability, the first or third embodiment may appropriately be employed.

<Fourth Embodiment>

In the first embodiment, the client 111 periodically polls the status from the device, and reflects the obtained status in the MAP display.

In a fourth embodiment, the client 111 obtains the status from the device by event notice, and reflects the obtained status in the MAP display.

In the periodical polling for obtaining the device status as in the first embodiment, even when the packet is temporarily lost on the network, the device status can securely be obtained.

On the other hand, in the obtaining of the status by the event notice from the device as in the fourth embodiment, as compared with the obtaining by the polling, the network traffic can effectively be reduced. Therefore, considering the certainty of the status obtaining, network load, and the like, the first or fourth embodiment may be selected.

Since the fourth embodiment is based on the first

09612565-070700

embodiment, mainly the respects different from the first embodiment will be described hereinafter.

First, the client 111 transmits an event notice destination registration request shown in Fig. 51 to
5 the device to receive an event notice from the device.

The event notice destination registration request includes notice condition information indicating the occurrence of an event requiring the event notice, and event notice destination information indicating the
10 notice destination.

In an example of Fig. 51, the issuer of the event notice destination registration request (the device indicated by the search result from the server 112) is the color LBP 101, "paper empty" and "paper jam" are
15 set to the notice condition information, and the IP address indicating the client (client 111) is set to the event notice destination information.

On the other hand, the device (color LBP 101) holds the received event notice destination
20 registration request (Fig. 51) in an event notice destination management table shown in Fig. 52. In the event notice destination management table, the event notice destination address, network protocol for notifying the event, and event condition to be notified
25 are associated and stored.

Furthermore, for the event notice destination address described in the received event notice

09612555-070700

destination registration request (Fig. 51), a response
(registration end) of event notice destination
registration is returned as shown in Fig. 53. Thereby,
in the client having ended the registration, the icon
5 indicating the status at the time is displayed as the
initial state of icon display (until a first event
notice is issued from the device).

Then, in the color LBP 101, for example, when
paper runs out, the information (event notice
10 destination information or the like) of the client for
the event notice is obtained from the event notice
destination held in the event notice destination
management table (Fig. 52), and the event notice is
issued to the client (here, client 111), for example,
15 as shown in Fig. 54.

As shown in Fig. 54, the event notice includes
icon information corresponding to the event generated
in the device (icon information indicating occurrence
of paper shortage), and the location information of the
20 device.

The process of the client 111 will next be
described with reference to flowcharts of Figs. 55 to
57.

Fig. 55 is a flowchart showing the general process
25 of the client 111, and processings of steps S5507 and
S5508 are added to the flowchart of the first
embodiment (Fig. 29).

09612565-070700

It is judged in the step S5507 whether or not the obtained event is the event notice from the device.

As a result of judgment of the step S5507, when the obtained event is the event notice, the process
5 advances to step S5508 to execute an event notice reception processing including an processing of changing the icon on MAP displayed on the CRT 210.

Here, the event notice reception processing of the step S5508 of Fig. 55 is executed based on the
10 flowchart shown in Fig. 57, and a search result processing of step S5506, that is, a process for processing the search result received from the server 112 is executed based on the flowchart shown in Fig. 56.

15 The search result processing in the client 111 (step S5506 of Fig. 55) will be described hereinafter with reference to Fig. 56.

It is first judged according to the search result from the server 112 whether or not one or more devices
20 are found (step S5601).

As a result of judgment of the step S5601, when the device is not found, a message indicating that is displayed on the CRT 210 (step S5615).

Thereafter, the present processing ends.

25 As a result of judgment of the step S5601, when the device is found, the search result is held in the hard disk drive (HDD) 211 (step S5602). Therefore, for

09612565-070700

Thereafter, with respect to the respective search results saved in the hard disk drive (HDD) 211, the subsequent processing steps are executed.

10 As a result of the judgment, when all the search results are processed, the present processing ends. If not, the processing is continuously executed from the next step S5604.

Subsequently, the IP address of the device information obtained in the step S5604 is used as the address, and the event notice destination registration request (event notice destination registration packet) is transmitted as shown in Fig. 24 (step S5605).

Thereafter, the CPU waits for a response packet (registration end) to the event notice destination

427 overlaps and displays the icon obtained in the step S5607 in the position indicated by coordinate information MAP of the device information on the MAP (step S5611).

5 Therefore, for example, with the processing for the device information shown in Fig. 13, since the BL information is "2-1", MAP information MP2-1 shown in Fig. 16 is displayed as MAP on the CRT 210, and the icon indicating the operated status is displayed in the position indicated by the coordinate information MAP (= 10X+10Y) on the MAP.

 Thereafter, the CPU returns to the step S5603 to execute the processing for the next search result, and repeatedly executes the subsequent processing step.

15 As a result of judgment of the step S5609, when the MAP is not displayed on the CRT 210, the display unit 427 displays MAP on the CRT 210 (step S5610).

 Thereafter, the CPU advances to the step S5611, and executes a processing for overlapping and displaying the icon on the MAP.

 As a result of judgment of the step S5608, when MAP display is impossible, it is judged whether or not unknown MAP information shown in Fig. 18 is now displayed on the CRT 210 (step S5612).

25 As a result of judgment of the step S5612, when the unknown MAP is displayed on the CRT 210, the icon obtained in the step S5607 is displayed in the device

09612565 070700

column (column "2902" of Fig. 18) on the unknown MAP (step S5614). As a result, the icon of the device whose location information is unregistered is displayed in the device column on the unknown MAP.

5 Thereafter, the CPU returns to the step S5603 to execute the processing for the next search result, and repeatedly executes the subsequent processing step.

 As a result of judgment of the step S5612, when the unknown MAP is not displayed on the CRT 210, the
10 unknown MAP is displayed on the CRT 210 (step S5613).

 Thereafter, the CPU advances to the step S5614, and executes a processing for displaying the icon in the icon column of the MAP.

 A search result processing in the client 111 (step
15 S5508 of Fig. 55) will be described hereinafter with reference to Fig. 57.

 First, the event notice (see Fig. 54) is received from the device in which the event notice destination registration is performed by the processing of steps
20 S5605 and S5506 of Fig. 55, and the icon information included in the event notice is obtained (step S5701).

 Moreover, the location information of the device included in the event notice is obtained (step S5702).

 Subsequently, it is judged whether or not the
25 device information including the information matching with the location information obtained in the step S5702 is present in the search result (search result

09612565-070700

As a result of the judgment, when there is no
5 matching device information, the present processing
ends as it is. When the matching device information is
present, the processing of the next step S5703 is
executed.

15 Thereby, for example, when the screen shown in Fig. 22 is displayed, and the paper shortage occurs in the color LBP 101, the icon of the color LBP 101 in the screen of Fig. 22 is changed to the icon as shown in Fig. 26 for display.

The device process will next be described with reference to flowcharts of Figs. 58, 59. Fig. 58 is a flowchart showing the event notice destination registration process of the device.

25 Here, for the simplicity of the description, the
color LBP 101 is noted among various devices, and the
event notice destination registration process will be

In the color LBP 101, when power turns on, first the CPU 2302 opens the receiving port to receive the event notice destination registration request (status

By the processing of the step S5801, when the event notice destination registration request from a certain client is received (step S5802), the notice condition included in the event notice destination registration request and notice destination information are managed by a table as shown in Fig. 52 (event notice destination table) (step S5803).

Subsequently, the response packet is transmitted to the client (step S5806).

Fig. 58 is a flowchart showing a device event notice processing.

Additionally, the processing stays in the present

step until the event occurrence of the status change is detected.

Subsequently, the notice condition and event notice destination held by the step S5803 of Fig. 58
5 are referred to, and the client to which the event notice is to be transmitted, that is, the client to be notified of the currently occurring event is grasped (step S5902).

Subsequently, as a result of processing of the
10 step S5902, it is judged whether or not the client to be notified exists (step S5903).

As a result of the judgment, when there is no client to be notified, the present processing ends.
When the client to be notified exists, the next step
15 S5904 is executed.

As a result of judgment of the step S5903, when the client to be notified exists, an event notice packet (see Fig. 54) including event information is prepared (step S5904). Subsequently, the event notice
20 prepared in the step S5904 is transmitted to all the clients to be notified (step S5905).

Thereafter, the present processing ends.

Additionally, in the fourth embodiment, the layout bit map held by the client has been described, but as
25 in the third embodiment, the server may hold the layout bit map, so that the layout bit map is appropriately transmitted to the client in response to the request

09612565 070700

from the client.

In this case, in the step S5610 of the search
result processing (Fig. 56) of the client 111, by
notifying the BL information to the server 112, the
5 layout bit map corresponding to the BL information is
obtained from the server 112.

As described above, in the present embodiment, in
the clients 111, 113, by obtaining the position
information of the device matching with the search
10 condition designated by the user, and displaying the
device icon on the MAP, the user can easily recognize
the device and the position of the device.

Particularly, in the present embodiment, since the
icon on the MAP is changed in accordance with the
15 corresponding device status (operating, paper shortage,
paper jammed, no toner, door open, and the like), the
user can visually and easily know the device status.
Therefore, the user can efficiently select and use the
usable device.

Moreover, in the present embodiment, since in the
20 clients 111, 113, the icon information (device bit map
icon information) indicating the device status is
directly obtained from the device during the event
notice destination registration to the device (during
25 reception of the response) or during reception of the
event notice from the device, it is unnecessary to hold
beforehand the icon information indicating various

09613565-070700

statuses of the device in the server 112 and clients 111, 113. This can prevent the memory resources of the server 112 and clients 111, 113 from being consumed. Moreover, when a large number of clients exist, it is unnecessary to install the icon information in the
5 respective clients. Therefore, the user's burden on the client side can be lightened, and the device in the unknown status effectively fails to be displayed.

Additionally, for the form in which the icon data
10 and hierarchical position information of the stored device are transmitted onto the network, the application to other various forms can be considered.

For example, in the network system provided with no directory server, when the device responds to
15 Broadcast or Multicast by device search protocols such as SLP from the computer on the network, the hierarchical position information may be set to the response packet. Subsequently, on the computer side having received the response packet, the icon data is
20 displayed on the layout bit map based on the received hierarchical position information.

Additionally, in the above-described embodiments, the icon indicating the device is displayed on the MAP, but this is not limited, and character information may
25 further be displayed as the information indicating the device.

Moreover, in the respective embodiments, the icon

09612565 1070700

indicating the device is displayed/outputted on the screen on the MAP, but this is not limited, and for example, the print output, or the like may be performed so that the user can visually grasp the position, status, and the like of the device.

Furthermore, the device search system can be realized using a technique utilized, for example, in WWW technique. In this case, the server 112 is provided with a WWW server function, a database function (DBMS), and a gateway function as an intermediate between WWW server and DBMS. The WWW server supplies a search screen constituted of HTML or XML to the client.

The client displays the search screen supplied from the WWW server by browser software, and the user executes the device search using the displayed search screen.

Furthermore, various data (MAP, icon, and the like) exchanged with the server, client, and device are constituted of HTML, XML, and the like, and HTTP is used in the protocol for exchanging the data.

Moreover, on the client side, to realize the function not disposed on the general-purpose browser software, for example, Applet as one of JAVA techniques is utilized.

Additionally, the network device control program for executing the above-described processes of the

09612565-070700

respective embodiments may be executed in PC 200 (see Fig. 2) by the program installed from the outside.

In this case, when a group of information including the program is supplied to the PC 200 via outside storage media such as CD-ROM, flash memory, and floppy disk, or networks such as electronic mail and personal computer communication, and the information group is loaded onto the PC 200, the present invention can be applied.

Fig. 47 shows the memory map of CD-ROM as one example of the storage media.

In Fig. 47, in an area "9999", the address information of an area 9998 in which the subsequent installation program is stored, and an area 9997 in which a network device control program is stored are stored as directory information.

Therefore, when the network control program is installed in the PC 200, first the installation program of the area 9998 is loaded in the PC 200 and executed by the CPU 202. By executing the installation program, the network device control program is read from the area 9997 and stored in the hard disk drive (HDD) 211. Thereafter, when the CPU 202 reads the program from the hard disk drive (HDD) 211 and executes the program, the functions of the respective embodiments are realized.

Moreover, in the above-described embodiments, the computer apparatus has been illustrated as the example

09612565-070700

of the client apparatus 111 or the server apparatus 112, but the devices such as a scanner, a facsimile machine, and a printer may be provided with the function of the client apparatus or the server apparatus.

For example, by providing the scanner with the function of the client apparatus, the user can easily know the status of the printer for printing the original data read by the scanner, or the status of the facsimile apparatus for transmitting the original data read by the scanner.

Moreover, it goes without saying that the object of the present invention is also attained by supplying the storage medium for storing the software program code to realize the above-described functions of the embodiments to the system or the apparatus, and reading and executing the program code stored in the storage medium by the system or the apparatus computer (or CPU or MPU).

In this case, the program code itself read from the storage medium realizes the inventive functions of the present invention, and the storage medium for storing the program code constitutes the present invention.

As the storage medium for supplying the program code, for example, a floppy disk, hard disk, optical disk, optical magnetic disk, CD-ROM, CD-R, magnetic

09612565-070700

tape, nonvolatile memory card, ROM, and the like can be used.

Moreover, it goes without saying that the above-described embodiment functions can be realized not only
5 by executing the program code read by the computer but also by performing a part or the whole of the actual processing by the operating system (OS), and the like operating on the computer based on the instruction of the program code.

10 Furthermore, it goes without saying the above-described embodiment functions can be realized by writing the program code read from the storage medium into a function expansion board inserted to the computer or a memory disposed in the function expansion
15 unit connected to the computer, and performing a part or the whole of the actual processing by the CPU, and the like disposed in the function expansion board or the function expansion unit.

09612565.070700